

# EasyOpen® WC



*CS EasyOpen with NewYorker door and LaviLock*



*EasyOpen with flush door*



*AutoCav WC with NewYorker*



*EasyOpen with CL400 ADA*



## Features

The **CS EasyOpen®** door system was initially developed to provide council compliant access to toilets for the disabled. It is now also commonly specified when large 'D' type handles or hardware that protrudes from the face of the door are required.

The cavity pocket is cut short by 100mm, enabling the door to protrude 100mm.

- One toilet can be used by everybody.
- Supplied fully assembled, ready for on-site installation.
- All aluminium components screwed together for strength and reliability.
- Maximum door weight: 240kg.
- Fully compliant when a 910mm wide door is used. For increased clear walk-through, a door leaf width of 1050mm may be more suitable.

## Technical Information

Useful formulas ([online calculator www.csfordoors.co.nz](http://www.csfordoors.co.nz))

Dimension Required	Manual	Auto
Trim height*	DH + 95	DH + 260
Trim width*	DW x 2 - 70	DW x 2 + 30#
Distance between jambs*	DW - 31	DW - 31
Clear walk through	DW - 131	DW - 31#
Distance over jambs (Arch)	DW + 13	DW + 13
Distance over jambs (Grvd)	DW + 31	DW + 31
Distance over jambs (Alum)	DW + 31	DW + 31
Floor to top of head (Arch)	DH + 38.5	DH + 38.5
Floor to top of head (Grvd)	DH + 49.5	DH + 49.5
Floor to top of head (Alum)	DH + 44	DH + 44
Floor to underside of head*	DH + 18.5	DH + 18.5
Floor to u/s of head (Alum)	DH + 13.5	DH + 13.5

All dimensions in millimetres. DH=Door Height, DW=Door Width  
 \* = Same calculations for Architrave (Arch) & Grooved (Grvd) jambs  
 # Auto doors slide back flush.

### How to specify (example)

Product:	~ CS EasyOpen by CS FOR DOORS
Location:	~ Toilet D801
Door leaf dimensions:	~ 2100mm x 1050mm
Door type:	~ Flush Solid Core
Door finish:	~ Paint
Jamb type & finish:	~ P/C Aluminium Titania
Framing material & size:	~ 90mm timber framing
Wall lining thickness:	~ 13mm
Door gear type:	~ CS 240kg track system
Handle type:	~ CL100 LaviLock

Full specifications are available on [www.masterspec.co.nz](http://www.masterspec.co.nz)

## Quality

Our aim is to manufacture the best sliding door systems available. Every component used within our products is uniquely designed with this in mind and backed by our manufacturer's guarantee.

**WE GUARANTEE PRODUCT WITH OUR SERIAL CODES FOR UP TO TEN YEARS\***

## Options

Incorporate any of the architectural detail options below with the CS EasyOpen cavity slider to create a specific look or to provide a unique solution to your design requirements.

### Configurations



Single

### Operation



Standard



AutoCav® WC

### Jamb Options



Architrave




Grooved



AluSealed®



Hi-Impact



ShadowLine



Full-Height



SquareStop



Custom

### Specialised

Ply panels  
Door Protrusion

H3 Components  
BraceWall®

### Hardware Options



**CL100 LaviLock™**

Available in Satin Chrome or Polished Brass



**CL400® ADA Magnetic**

Available in a range of finishes.